

# 9500 Bi-Folding Gates

Part of the

## 9500 BI-FOLDING GATE RANGE

### DESCRIPTION



PLUG & PLAY  
INSTALLATION

Speed Gates | Compliant | Plug & Play

- 100% duty cycle heavy industrial usage
- BS EN 12453 Peace of mind for safety
- Single Phase Supply
- Plug & Play installation
- Programmable control panel c/w fault diagnostic on screen display
- Highest specification of components are ONLY used
- Seamlessly forms part of the existing fence lines perimeter security
- Steel/Galvanised for long lasting and maintenance free performance
- MANY different infill's available to match clients exacting requirements
- Error log is stored in the control panel for fault diagnosis
- A VERY easy to use manual release mechanism which requires no tools in the event of power failure.

### 9500 ADDED BENEFITS

- Ease of installation
- Low maintenance
- 99.9% Access Control compat
- Fast operating gates
- Fire Alarm Input pre-configured
- Designed and built to last
- Easy to use for end users

### OPTIONAL EXTRAS

- Razor Wire Extensions
- Electric Fence
- Anti-Climb Spikes
- Traffic Lights
- Warning Siren
- Timber Infills
- Louvre Infills



### "INDUSTRY STANDARD"

Our gates have been classed as the best in the industry. It has been designed to last using the best materials and components that we can buy. As with all our products they are 100% Duty Cycle



### ABSOLUTE CONTROL

The 9500 Bi-Folding Gates feature a Feig control panel that is far more advanced for safety and motion than its rivals

**THE UK'S  
No1  
TRIED,  
TESTED  
& TRUSTED  
INDUSTRIAL  
GATES**

The 9500 Bi-Folding Trackless Speed Gates are the ideal solutions where speed of opening and closing is essential or where space is at a premium.

The 9500 bi-folding trackless speed gates typically open at more than twice the speed of a traditional swinging gates of the same size which ensures a fast throughput of traffic whilst maintaining security of the site.

The 9500 utilises a driven integrated frequency converter, single phase power, supplying a 3 phase motor, worm and wheel gearbox with a direct-drive shaft connected to the gate leaf, which ensures a smooth and positive movement. 9500 speed gates are rated for 100% duty cycle i.e. continuous operation.

A wide range of alternative infills are available to suit customers requirements and to match adjoining fencing design. Also available are spiked tops, warning lights and sirens if required.

The gates are supplied with a programmable logic control board which is mounted in the main pillar of the gate.

The 9500 Bi-Folding Gates comply with BS/EN 12453 (ALL automated gates must comply with the current legislation). We fit as standard a number of safety devices, including dual height photocells and category 2/3 safety edges.



# 9500 Bi-Folding Gates



## PRODUCT SPECIFICATION

### Gate Speed

3 to 8 Seconds

(Speed WILL vary dependant upon gate size/Infill etc)

### Duty Cycle

100% Heavy Industrial Usage

Suitable for Indoor & Outdoor Usage

### Specification

CE Approved, TUV Approved

### Power Requirements

Single Phase 240v 50Hz 10 Amps

### Colours

All RAL Colours Available

(Non Standard RAL's Optional Cost)

### Maximum Span Dimensions

10m Clear Drive Through Opening

### Maximum Height Dimensions

2.4 Metres (Max Width 10m)

3.0 Metres (Max Width 6m)

### Material Construction

Steel Construction of Gate Leaf and Main Tower

All Components are Galvanised OR Zinc Plated Steel

### Unit Weight

595Kg Approx

(dependant upon gates size and infill type)

\*All gates are bespoke and manufactured to order.

CAD Drawings provided as standard



Tech Support provided and FREE mobile APP as standard



PLUG & PLAY INSTALLATION

## Flashing Beacon

## Strong Secure Steel Tower with 7 Lever Safe Locks

## Emergency Stop Button & Deadman Keyswitch

## Quick & Easy Install

## Four Category 3 Safety Edges

## Dual Height Photocells

## Easy to Use Manual Release

